

Specification

General	TC-500
Frequency Range	350.2250 MHz 350.2375 MHz 350.2500 MHz 350.2625 MHz 350.3500 MHz 350.3625 MHz 350.3750 MHz 350.3750 MHz 350.3875 MHz 350.4000 MHz
Channel Capacity	10 Channels
(Factory Programmed)	
Channel Spacing	12.5 KHz
Operating Voltage	6V DC
Modulation Mode	F3E
Antenna Impedance	50
Dimension (mm)	108(L)x54.2(W)x37.4(H)
Weight	273g (with bat & Ant)
Battery	6V / 1100mAH Ni-Mh

Transmitter	TC-500
Output Power	1W / 4W
Frequency Stability	5ppm
Modulation Limiting	2.5 KHz
Modulation Distortion	5%
Spurious Emission	7.5W
Residual Frequency Modulation	40dB

Receiver	TC-500
Reference Sensitivity	0.25uV
AF output power	>0.5W
Audio Distortion	5%
Blocking	85dB
Adjacent Channel Selectivity	60dB
Intermediation Rejection	60dB
Spurious Response Rejection	60dB

Specification are subject to change without notice and range will vary depending on the geography and surrounding environment .







Your Local Dealers:



ISO9001:2000 Certificate NO:FM 61540

Shenzhen HYT Science & Technology Co., Ltd.

http://www.hyt.cn

HYT^{*} is the registered trademark of Shenzhen HYT Science & Technology Co., Ltd.


© 2004 HYT,Co.,Ltd. All Rights Reserved.

HYT retains right to change the product design and specification. Should any printing mistake occur, HYT doesn't bear relevant responsibility. Little difference between real product and product indicated by printingmaterials will occur by printing reason.





Economical Radio



1 1 10

TC-500

Budget & Practical Radio In Your Palm



HYL

The Newest TC-500 radio. as one of CBRS series, (Citizen Band Radio Series) inherits HYT excellent quality with minimum budget. Palm Size with non-keypad, lightweight and fully embody its wisdom. They are applicable for Car Racing, Hotel & Restaurant, Supermarket & Warehouse, Entertainment Sport, Tourism & Service Line. Retail & Wholesales Industry, Agriculture & Farming Industry, Minitype Construction Site and Residence Safeguard Management.

Main Features:

1W or 4W Carrier Output Power

10 Pre-programmed Channels

Palm Size, Compact Design

38 CTCSS, 83 CDCSS

It enables useronly hear calls from their own group for clearer, improved communication

6V / 1100mAH Ni-MH Battery, Battery Save, Low Battery Alert

Battery Save function can be turned on/ off by the dealer. This function minimizes the amount of power used when no signal is being received and no operation is being performed (no key is being pressed, and no switch is being turned) Average Battery Life: 12 Hr for 1W & 8 Hr for 4W

Time-out Timer(TOT)

If the transmission exceeds preset time, transmission will be stopped. This feature is used to prevent one from using the same channel for a long time

Priority Scan

Channel scanning provides users with an easy way tomonitor multiple channels for activity. The radio will scan the priority channel periodically while receiving a call on another non-priority channel





Busy Channel Lockout

Avoid Interference with the users using the same channel by preventing transmission if another talk group is already on the channel

Monitor Function

Press monitor keyto enable

Squelch Level Control

Higher squelch level avoids interference of noises and / or unwanted signals and Squelch Tail Elimination

VoiceOperated Transmission (VOX)

With the use of an appropriate headset, you can speak and listen to a radio conversation without having the use of your hands.